

SINGLE AND DOUBLE STAGE VACUUM PUMPS

Dual voltage design vacuum pump operations on 115 VAC or 230 VAC (50 or 60Hz). Advanced two-stage design pulls deep vacuum fast to 15 microns. Single stage design pulls vacuum fast to 100 microns. *Tap into rooftop power with an optional 230VAC jumper cable (VPXJ220).

PRO-SET®

NEW!

CE



Single Stage

Two Stage

Model	VP2S	VP3S	VP6S	VP2D	VP3D	VP6D
Free Air Displacement	1.9 CFM @ 60HZ 45 l/m @ 50Hz	3.15 CFM @ 60HZ 75 l/m @ 50Hz	6.25 CFM @ 60HZ 148 l/m @ 50Hz	1.9 CFM @ 60HZ 45 l/m @ 50Hz	3.15 CFM @ 60HZ 75 l/m @ 50Hz	1.9 CFM @ 60HZ 45 l/m @ 50Hz
Motor Dual Voltage (115/230 VAC 50/60 Hz)	1/4hp-1440 rpm (60Hz) 1720 rpm (50Hz)	1/3hp-1440 rpm (60Hz) 1720 rpm (50Hz)	1/2hp-2880 rpm (60Hz) 3440 rpm (50Hz)	1/4hp-1440 rpm (60Hz) 1720 rpm (50Hz)	1/3hp-1440 rpm (60Hz) 1720 rpm (50Hz)	1/2hp-1440 rpm (60Hz) 3440 rpm (50Hz)
Ultimate Vacuum	100 microns	100 microns	100 microns	15 microns	15 microns	15 microns
Intake Ports (male flare)	1/4", 3/8" & 1/2" ACME	1/4", 3/8" & 1/2" ACME	1/4", 3/8" & 1/2" ACME	1/4", 3/8" & 1/2" ACME	1/4", 3/8" & 1/2" ACME	1/4", 3/8" & 1/2" ACME
Oil Capacity	12 oz./350 ml	12 oz./350 ml	17 oz./500 ml	12 oz./ 350 ml	15 oz./ 450 ml	15 oz./ 450 ml
Dimensions	14 x 6.75 x 11.25	14 x 6.75 x 11.25	15.25 x 7 x 11.25	14 x 6.75 x 11.25	15.25 x 7 x 11.25	15.25 x 7 x 11.25
Shipping Weight	14.37 lb	16.58 lb	22.11 lb	19.90 lb	25.42 lb	26.53 lb

ANTI SIPHON VALVE KITS



The CPS patent pending anti-siphon valve is an essential accessory to any vacuum pump application. The anti-siphon valve prevents the cross-contamination of vacuum pump oil and the compressor oil in the A/C or refrigeration system being serviced. Mixing of vacuum pump oil and compressor oil can cause premature failure in the A/C or refrigeration system. CPS makes three models that fit all CPS and other brands of vacuum pumps.

VPASU

1/4" SAE,
3/8" SAE,
1/2"-20 UNF



VPAS4 1/4" SAE

VPAS8 3/8" SAE

